COMMERCIAL AXLE JACK

Product Data Sheet



Model 95A0911 - 95 Ton Capacity

CAGE CODE: 69134

Standard Features

■ ID chrome-plated plungers

 Hydraulic fuse prevents lowering load, in the event of a fluid line failure

Two manual hand pumps

high pressure, low volume

low pressure, high volume

Single valve control for raise and lower of aircraft

Control console with instruction decals

Oil filter cap with filtered air vent and dipstick

Swivel casters with retractable front caster

All non-painted parts are plated for corrosion resistance

1 year standard warranty

Optional Features (Add suffix to model #)

L: Load gauge for indication (Tons & PSIG)

R: Power retract

A: Air-operated hydraulic pump

H: Rain hat

E: Extended adaptor for B747-8



SPECIFICATIONS	<u>Standard</u>	<u>Metric</u>
Rated Capacity	95 tons	86 tons
Low Height	9.25 in	235 mm
Hydraulic Lift	10.88 in	276 mm
Extension Screw	4.75 in	121 mm
Total Extended Height	24.88 in	632 mm
Base Width	10 in	254 mm
Cylinder Diameter	9 in	229 mm
Oil Pressure at Rated Capacity	8,000 psig	562 kg/sq cm
Safety Pop-Off Valve Set At	101 tons	92 m tons
Proof Load	118 tons	107 m tons
Floor Loading at Rated Capacity	1,000 psi	70 kg/sq cm
Reservoir Capacity	5.5 gal	20.8 ltr
Hydraulic Fluid	MIL-PRF-5606 or equivalent	MIL-PRF-5606 or equivalent
Maximum Towing Speed	5 mph	8 km/h
Approximate Jack Net Weight	580 lbs	263 kg

Typical Aircraft Applications

Main Landing Gear
A300, A310, A319, A320,
A321, A330, A340-200/300/500/600, A350-900
B707, B717, B720, B727, B737,
B747, B747-8, B757, B767, B777,
B787, DC8, DC10, L1011, MD11

Nose Landing Gear
A300, A310, A330,
A340-200/-300/500/600,
A350, B727, B747, B747-8,
B757, B767, B787
DC10, L1011, MD11

TECHNICAL CONTACT

Manifold & Phalor, Inc. 10385 Busey Road Canal Winchester, Ohio 43110 Phone: 614.920.1200

Fax: 614.920.1205 Email: sales@manifoldphalor.com

SALES CONTACT

Don Palmore ATAP, Inc. 130 Industry Way Eastaboga, AL 36260 Phone: 800.362.2827 x188 Email: don.palmore@atap.com



www.manifoldphalor.com