SINGLE STAGE VARIABLE HEIGHT JACK

Product Data Sheet

Model 40T087.072 – 40 Ton Capacity

CAGE CODE: 69134

Standard Features

- Manual high/low pressure pump
- Heavy duty tow bar with heavy duty swivel casters and swivel locks
- Rain hat (covers upper head)
- Thermal relief valve to protect system due to internal expansion from temperature
- Hard chrome plated cylinder bore
- All unpainted parts are plated to resist corrosion
- Skydrol resistant paint (Safety Yellow Standard)
- Factory proof load 150% of rated capacity
- 2-year standard warranty
- Shipment on domestic skid

Optional Features

- Ladder & platform
- Platform mounted operating controls to allow one person to position locknut while raising and lowering
- Air operated hydraulic pump
- 1 ¼" Spherical radius male ship adapter
- Extended ³/₄" spherical radius female ship adapter
- Adjustable swivel feet with level
- Load gage (Tons/PSI)
- Customer specified paint color
- Export crating

| SPECIFICATIONS | Standard | Metric |
|---------------------------------|----------------------------|----------------------------|
| Rated Capacity | 40 tons | 36.3 m tons |
| Side Load Rating | 15% | 15% |
| Low Height | 87 in | 2,210 mm |
| Roll Under Height | 88.5 in | 2,248 mm |
| Hydraulic Lift | 72 in | 1,829 mm |
| Extension Screw | 26 in | 660 mm |
| Total Extended Height | 185 in | 4,699 mm |
| Oil Pressure at Rated Capacity | 1,591 psi | 112 kg/sq cm |
| Safety Pop-Off Valve Setting | 44 tons | 39.9 m tons |
| Proof Load | 60 tons | 54.4 m tons |
| Floor Loading at Rated Capacity | 323 psi | 22.6 kg/sq cm |
| Reservoir Capacity | 25 gal | 94 ltr |
| Hydraulic Fluid | MIL-PRF-5606 or equivalent | MIL-PRF-5606 or equivalent |
| Maximum Towing Speed | 5 mph | 8 kmh |
| Approximate Jack Net Weight | 2,200 lbs | 997 kg |

TECHNICAL CONTACT

Manifold & Phalor, Inc. 10385 Busey Road Canal Winchester, Ohio 43110 Phone: 614.920.1200 Fax: 614.920.1205 Email: sales@manifoldphalor.com SALES CONTACT Don Palmore ATAP, Inc. 130 Industry Way Eastaboga, AL 36260 Phone: 800.362.2827 x188 Email: don.palmore@atap.com





Typical Aircraft Applications

FORWARD

A300*, A310*, A330*, A340* A350*, 747, 757, 767, 777*/** 787, DC10, MD11, L1011

MAIN

A318***, A319***, A320*** ATR42, ATR72, C130, C Series

*For shoring and wing only **Use ³⁄₄" spherical adapter P/N ***Use 1 ¹⁄₄" spherical adapter P/N



Manifold & Phalor

www.manifoldphalor.com

SINGLE STAGE VARIABLE HEIGHT JACK

Continued

Model 40T087.072 - 40 Ton Capacity

CAGE CODE: 69134

Optional Features (Add suffix to model #)

- LP: Ladder & platform
- PMC: Platform mounted operating controls
- AP: Air operated hydraulic pump
- SA1: 1 ¼" Male spherical radius ship adapter
- SA2: ³/₄" Extended female radius ship adapter
- SF: Adjustable swivel foot
- LG: Load gage (Tons/PSI)
- CSP: Customer specified paint color

Packaging Options (Add suffix to model #) KD: Jack shipped knocked down domestic skid ECKD: Jack shipped knocked down international crate

TECHNICAL CONTACT Manifold & Phalor, Inc. 10385 Busey Road Canal Winchester, Ohio 43110 Phone: 614.920.1200 Fax: 614.920.1205 Email: sales@manifoldphalor.com SALES CONTACT Don Palmore ATAP, Inc. 130 Industry Way Eastaboga, AL 36260 Phone: 800.362.2827 x188 Email: don.palmore@atap.com



Manifold & Phalor

www.manifoldphalor.com



