

# SINGLE STAGE FIXED HEIGHT JACK

## Product Data Sheet



## Model 20T093.040 – 20 Ton Capacity

CAGE CODE: 69134



### Standard Features

- Manual high/low pressure pump
- Heavy duty swivel casters
- Rain hat (covers upper head)
- Thermal relief valve to protect system due to internal expansion from temperature
- Hard chrome plated cylinder bore
- All unpainted parts are plated to resist corrosion
- Skydrol resistant paint (Safety Yellow Standard)
- Factory proof load 150% of rated capacity
- 2-year standard warranty
- Shipment on domestic skid

### Optional Features

- Air operated hydraulic pump
- Platform mounted operating controls to allow one person to position locknut while raising and lowering
- Ladder and platform
- Load gage (Tons/PSI)
- Heavy duty tow handle
- Customer specified paint color
- Export crating

### SPECIFICATIONS

	<u>Standard</u>	<u>Metric</u>
Rated Capacity	20 tons	18.1 m tons
Side Load Rating	15%	15%
Low Height	93 in	2,362 mm
Roll Under Height	94 in	2,387 mm
Hydraulic Lift	40 in	1,016 mm
Extension Screw	10 in	254 mm
Total Extended Height	143 in	3,632 mm
Oil Pressure at Rated Capacity	1,683 psi	118.3 kg/sq cm
Safety Pop-Off Valve Setting	22 tons	20 m tons
Proof Load	30 tons	27.2 m tons
Floor Loading at Rated Capacity	100 psi	7 kg/sq cm
Reservoir Capacity	3 gal	11 ltr
Hydraulic Fluid	MIL-PRF-5606 or equivalent	MIL-PRF-5606 or equivalent
Maximum Towing Speed	5 mph	8 kmh
Approximate Jack Net Weight	750 lbs	340 kg

### Typical Aircraft Applications

#### MAIN

F27, F50, RRJ95, SSJ100

#### AFT

737, RJ190/195

#### TECHNICAL CONTACT

Manifold & Phalor, Inc.  
10385 Busey Road  
Canal Winchester, Ohio 43110  
Phone: 614.920.1200  
Fax: 614.920.1205  
Email: sales@manifoldphalor.com

#### SALES CONTACT

Don Palmore  
ATAP, Inc.  
130 Industry Way  
Eastaboga, AL 36260  
Phone: 800.362.2827 x188  
Email: don.palmore@atap.com



**Manifold  
& Phalor**

www.manifoldphalor.com

# SINGLE STAGE FIXED HEIGHT JACK

Continued



## Model 20T093.040 – 20 Ton Capacity

CAGE CODE: 69134



### Optional Features *(Add suffix to model #)*

- AP: Air operated hydraulic pump
- LP: Ladder & platform
- PMC: Platform mounted operating controls
- LG: Load gage (Tons/PSI)
- TH: Heavy duty tow handle
- CSP: Customer specified paint color

### Packaging Options *(Add suffix to model #)*

Standard shipping condition assembled on skid (incl)

KD: Jack shipped knocked down domestic skid

EC: Jack shipped assembled in international crate

ECKD: Jack shipped knocked down international crate

#### TECHNICAL CONTACT

Manifold & Phalor, Inc.  
10385 Busey Road  
Canal Winchester, Ohio 43110  
Phone: 614.920.1200  
Fax: 614.920.1205  
Email: [sales@manifoldphalor.com](mailto:sales@manifoldphalor.com)

#### SALES CONTACT

Don Palmore  
ATAP, Inc.  
130 Industry Way  
Eastaboga, AL 36260  
Phone: 800.362.2827 x188  
Email: [don.palmore@atap.com](mailto:don.palmore@atap.com)



**Manifold  
& Phalor**

[www.manifoldphalor.com](http://www.manifoldphalor.com)