

SINGLE STAGE FIXED HEIGHT JACK

Product Data Sheet



Model 30T099.082 – 30 Ton Capacity

CAGE CODE: 69134

Standard Features

- Manual high/low pressure pump
- Heavy duty tow bar with heavy duty swivel casters and swivel locks
- Rain hat (covers upper head)
- Thermal relief valve to protect system due to internal expansion from temperature
- Hard chrome plated cylinder bore
- All unpainted parts are plated to resist corrosion
- Skydrol resistant paint (Safety Yellow Standard)
- Factory proof load 150% of rated capacity
- 2-year standard warranty
- Shipment on domestic skid

Optional Features

- Air operated hydraulic pump
- Platform mounted operating controls to allow one person to position locknut while raising and lowering
- Ladder/platform
- Load gage (Tons/PSI)
- Customer specified paint color
- Export crating



SPECIFICATIONS

	<u>Standard</u>	<u>Metric</u>
Rated Capacity	30 tons	27.2 m tons
Side Load Rating	15%	15%
Low Height	99 in	2,515 mm
Roll Under Height	100.5 in	2,553 mm
Hydraulic Lift	82 in	2,083 mm
Extension Screw	32 in	813 mm
Total Extended Height	213 in	5,410 mm
Oil Pressure at Rated Capacity	1,193 psi	84 kg/sq cm
Safety Pop-Off Valve Setting	33 tons	29.9 m tons
Proof Load	45 tons	40.8 m tons
Floor Loading at Rated Capacity	242 psi	17 kg/sq cm
Reservoir Capacity	16 gal	61 ltr
Hydraulic Fluid	MIL-PRF-5606 or equivalent	MIL-PRF-5606 or equivalent
Maximum Towing Speed	5 mph	8 kmh
Approximate Jack Net Weight	2,000 lbs	907 kg

Typical Aircraft Applications

FORWARD

A300*, A310*, A330*, A340*,
A350, 747*, 757, 767, 777

MAIN

A321NEO-LR, Q400

AFT

A318, A319, A320, A321, 737

**For roll under clearance, OLEO's
may need to be extended*

TECHNICAL CONTACT

Manifold & Phalor, Inc.
10385 Busey Road
Canal Winchester, Ohio 43110
Phone: 614.920.1200
Fax: 614.920.1205
Email: sales@manifoldphalor.com

SALES CONTACT

Don Palmore
ATAP, Inc.
130 Industry Way
Eastaboga, AL 36260
Phone: 800.362.2827 x188
Email: don.palmore@atap.com



**Manifold
& Phalor**

www.manifoldphalor.com

SINGLE STAGE FIXED HEIGHT JACK

Continued



Model 30T099.082 – 30 Ton Capacity

CAGE CODE: 69134



Optional Features *(Add suffix to model #)*

- AP: Air operated hydraulic pump
- PMC: Platform mounted operating controls
- LP: Ladder and platform
- SF: Adjustable swivel foot
- LG: Load gage (Tons/PSI)
- CSP: Customer specified paint color

Packaging Options *(Add suffix to model #)*

KD: Jack shipped knocked down domestic skid

ECKD: Jack shipped knocked down international crate

TECHNICAL CONTACT

Manifold & Phalor, Inc.
10385 Busey Road
Canal Winchester, Ohio 43110
Phone: 614.920.1200
Fax: 614.920.1205
Email: sales@manifoldphalor.com

SALES CONTACT

Don Palmore
ATAP, Inc.
130 Industry Way
Eastaboga, AL 36260
Phone: 800.362.2827 x188
Email: don.palmore@atap.com



**Manifold
& Phalor**

www.manifoldphalor.com